



Recommended Rate Spreader Settings

16-4-8 Turf Rally™

Spreader	FAIRWAY GRADE			GREENS GRADE		
	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 6.25 lbs per 1,000 FT ²	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 3.12 lbs per 1,000 FT ²
Scott R8	3	10	L ½	3	10	I
Spyker / Best	3	9	5.1	3	9	3.7
Lesco	3	10	J or 22	3	10	E ½ or 13
Lely (1250)	4.5	34	6 ¼	4.5	30	4 ½
Accupro 2000	3	10	M ½	3	10	J
Earthway	3	10	19 ½	3	10	14 ½
Vicon (03 series)	4.5	28	38	4.5	22	20

7-7-7 Seven Iron™

Spreader	FAIRWAY GRADE			GREENS GRADE		
	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 10 lbs per 1,000 FT ²	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 8 lbs per 1,000 FT ²
Scott R8	3	10	O	3	10	K ¾
Spyker / Best	3	9	5.7	3	9	4.6
Lesco	3	10	K ¾ or 25 ½	3	10	H ½ or 19
Lely (1250)	4.5	34	6 ¾	4.5	30	5 ¾
Accupro 2000	3	10	P	3	10	L ¾
Earthway	3	10	23 ½	3	10	18
Vicon (03 series)	4.5	24	39	4.5	22	30

10-2-4 All Natural Organic™

Spreader	FAIRWAY GRADE			GREENS GRADE		
	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 10 lbs per 1,000 FT ²	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 5 lbs per 1,000 FT ²
Scott R8	3	10	* Q <small>5 LB Rate / make two passes</small>	3	10	O ½
Spyker / Best	3	9	8.3	3	9	5.4
Lesco	3	10	* M or 28 <small>5 LB Rate / make two passes</small>	3	10	K or 24
Lely (1250)	4.5	30	9	4.5	28	5 ¾
Accupro 2000	3	10	* R <small>5 LB Rate / make two passes</small>	3	10	P ½
Earthway	3	10	24 ½	3	10	22 ½
Vicon (03 series)	4.5	24	57	4.5	18	31

8-4-16 Endurance™

Spreader	FAIRWAY GRADE			GREENS GRADE		
	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 10 lbs per 1,000 FT ²	Ground Speed / MPH	Width of Coverage / FT	Setting for the recommended rate of 5 lbs per 1,000 FT ²
Scott R8	3	10	N ¼	3	10	K
Spyker / Best	3	9	5.5	3	9	4.2
Lesco	3	10	K ½ or 25	3	10	F ¾ or 15 ½
Lely (1250)	4.5	34	7 ¼	4.5	30	5 ¼
Accupro 2000	3	10	O ¼	3	10	L
Earthway	3	10	21 ½	3	10	15 ½
Vicon (03 series)	4.5	30	42	4.5	24	26

Water in thoroughly after application to help speed up breakdown. These suggested settings are only intended to aid your own calculations by providing a starting point; They are NOT intended to replace your own calibration. Please calibrate your spreader before applying product.